

## Technical Document – Cocoa Matting



This product is intended for use in surface-mounted applications with attached nosing on all 4 sides of the product and must be installed by professional installers that have sufficient professional liability insurance coverage (aka Errors and Omissions Insurance) for the project. Caution should be used in the moving and lifting of oversized, heavy entrance matting products. Allow for appropriate equipment and manpower to safely move materials. Work safe and always follow the relevant safety procedures.

Matter Surfaces recommends installing and maintaining entrance matting at all outdoor entrances; this will improve air quality, reduce maintenance costs, and lengthen the life of your floors.

Proper glides must be used on all furniture that may slide directly across this product; heavy objects must not be moved directly across the floor - use protective boards.

Do not install any material that has visible defects or damage. A contractor that installs any material that has visible defects or damage assumes responsibility for the damaged material.

All Safety Data Sheets (SDS), Installation, Maintenance and Warranty requirements must be read, understood and followed.

These instructions supersede any verbal or written instructions from Matter Surface representatives and must be followed for the limited warranty to be in effect.

### Technical Specifications

Roll Size		6'7" x approximately 39'4"
Overall Thickness	ISO 1765	½" (13mm), ⅝" (17mm), ¾" (20mm), 1" (23mm)
Material Composition		100% machine-spun coconut fiber yarn
Backing		PVC with integrated scrim
Number of Stitches	ISO 1763	45 / yd <sup>2</sup>
Custom Sizes		6'7" x custom lengths up to 39'4"
Colors		Natural, brown, charcoal, dark gray, medium gray, red, blue, green, burgundy & light gray
Color by Thickness		Natural available in ½", ⅝", ¾" and 1"; other colors available in ⅝" only
Total Weight	ISO 8543	13mm – 9.9 lbs/yd <sup>2</sup> ; 17mm – 10.4 lb/yd <sup>2</sup> , 20mm – 11.3 lb/yd <sup>2</sup> , 23mm – 12.2 lb/yd <sup>2</sup>
Pile Height	ISO 1766	13mm – 10mm, 17mm – 14mm, 20mm – 17mm, 23mm – 20mm
Surface Flammability	D 2859; DOC FF1-70	Pass
Warranty		Six months limited warranty