

Design Tile



Features

- Flexible, hidden interlocking, loose-lay LVT with a ceramic looking finish that is ideal for renovations and high traffic applications
- Available in modern designs and with unique color matching grout edging, providing ceramic aesthetics and vinyl performance

Specifications

Material	A heterogeneous vinyl flooring tile with a durable polyurethane wear layer
Tile Size	18" x 18": (457 mm x 457 mm) 24" x 24": (614 mm x 614 mm)
Case Pack	18" x 18": 5 tiles/case (11.19 sq ft/case) 24" x 24": 3 tiles/case (12.16 sq ft/case)
Thickness	7.8 mm
Total Weight	2.46 lbs/sq ft



Color Options

1500



1544 | Shalestone



1545 | Clay




1546 | Granite



1547 | Volcano



1548 | Limestone



1549 | Polished Concrete




1550 | Vintage Maple




1551 | Vintage Sand



1552 | Vintage Ash



1553 | Terrazzo Cream



1554 | Terrazzo Grey



1555 | Sandstone

1600



1692 | Manhattan Storm



1693 | Manhattan Grey




1694 | Manhattan Dust



1695 | Manhattan Cloud



1697 | Acero Beige



1698 | Marmetta Beige



1699 | Luberon Grey



1696 | Acero Light

Classification & Performances

Classification

Norm/Product Specification	—	—	EN ISO 10582
European Classification	EN ISO 10874	Class	34 - 43
Fire Rating	EN 13501-1	Class	Bfl - s1
Static Electrical Propensity	EN 1815	kV	< 2
Slip Resistance Wet	EN 16165 app.B (DIN 51 130)	Class	R10

Performances

Water Resistance	EN 660.2	mm ³	≤ 2.0
Wear Group	—	group	T
Type Binder Content	ISO 10582	group	I
Curling	EN ISO 23999	mm	≤ 1
Dimensional Stability (norm)	EN ISO 23999	%	≤ 0.15
Residual Indentation	EN ISO 24343-1	mm	≤ 0.05
Castor Chair Test	ISO 4918	—	OK
Shore Hardness	EN ISO 868	H _o	> 60
Thermal Conductivity	EN ISO 10456	W/(m.k)	0.25
Colour Fastness	EN 20 105 - B02	degree	≥ 6
Surface Treatment	—	—	PUR+
Chemical Product Resistance ⁽¹⁾	EN ISO 26987	—	OK

Environmental/Indoor Air Quality

TVOC after 28 days	ISO 16000-6	micrograms/m ³	< 100
--------------------	-------------	---------------------------	-------