

Graffiti

Product Description

A beautiful and practical walk-off entrance matting made with 100% polypropylene fibers, backed in high-density rubber. Plush matting in high impact colors, ideal for stand-out logo mats.

General Information

This product is ideal for high aesthetic, colorful design, fibered flooring used as loose-laid matting, and must be used for interior applications only. Mats Inc. recommends installing and maintaining entrance matting at all outdoor entrances; this will improve air quality, reduce maintenance costs, and lengthen the life of your floors.

Proper glides must be used on all furniture that may slide directly across the floor. Heavy objects must not be moved directly across the floor; remove the matting first.

Direct sunlight can cause UV damage (fading or bleaching) to most interior finishes, so Low E glass should be selected that will reduce the UV transmission to less than 1%. If not, applying 3M™ protection film (or similar) on the windows is recommended

Roll Size	~ 6'7" & 13'2" widths x 68'8" in length
Pile Weight	~ 5.9 oz./ ft. ² (1800 g/m ²)
Total Weight	~ 9.0 oz./ ft. ² (2760 g/m ²)
Overall Thickness	~ 1/2" (12.5 mm)
Pile Thickness	~ 5/16" (8 mm)
Backing	High Density Rubber
Limited Warranty	3 years

Performance

Color Stability to Rubbing	Tested wet and dry	None	Δ (Delta) E ≤ 0.4
Color Stability to Light	ISO 105-B02	None	Δ (Delta) E ≤ 0.5
Color Stability to Water	ISO 105-E01	None	Δ (Delta) E ≤ 0.4
Color Stability to Soiling	EN 1296	None	Δ (Delta) E ≤ 0.3
Dimensional Stability	ISO 2551	None	≤ 1.2% shrinkage, ≤ 0.5% expansion
Antistatic Behavior	ISO 6356	None	< 2kV