

Mats Inc. Maintenance Instructions

SaniPath

These instructions supersede any verbal or written instructions from Mats Inc. representatives, and must be followed in order for the warranty to be in effect.

Overall

Safety: Always post “Wet floor” and/or “Caution” tape when wet maintenance is going to be performed. Refer to cleaners’ MSDS for any Personal Protective Equipment requirements.

- **Actions not to take:** SaniPath does not require waxing, buffing, or stripping. Therefore, there is no need to apply any type of floor finishes or waxes.

Routine Cleaning

1. Shake dirt from mat and remove mat from service area.
2. Sweep and/or dust mop or vacuum (with heavy-duty commercial vacuum) the floor to remove all dirt and grit. **This is the single most important maintenance activity for preserving the floor’s appearance and performance – and typically the most overlooked and omitted.**
3. If needed, flush both sides of mat with warm water to remove remaining dirt.
4. Allow mat to dry flat before placing it back into service.

Deep Cleaning

Severely soiled matting can be restored to a high level of appearance with one of the following cleaning methods:

- Pre-spray mat with a low foaming, all-purpose cleaner. (For heavy grease buildup, use a water-based cleaner-degreaser.) Allow cleaning solution to dwell on mat for 3 to 5 minutes. Brush with a nylon bristle scrub brush. Flush mat with hot water and allow to dry flat before placing it back into service.

-OR-

- Clean the mat using a high-pressure washer with a low foaming general purpose cleaner. Flush mat with hot water and allow to dry flat before placing it back into service.